

# absolute coatings, inc.

38 Portman Road  
New Rochelle, NY 10801  
(800) 221-8010 (914) 636-0700

## MATERIAL SAFETY DATA SHEET

Ultra Gold Wood Floor Finish 275 VOC

GLOSS #92001 #92004

### QUICK IDENTIFIER

Health	1	Reactivity	1
Flammability	0	Protective Equipment	G

### EMERGENCY PHONE # FOR CHEMICAL SPILLS, LEAKS, OR EXPOSURE:

CHEMTEL: 800-255-3924 (24 HRS.) Nat'l. Poison Control Center: 800-222-1222

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.

HAZARDOUS MATERIALS INFORMATION LABEL (HMIS)

HAZARDOUS CODE: 4 = Extreme, 3 = High, 2 = Moderate, 1 = Slight, 0 = Insignificant

PERSONAL PROTECTION: G = Synthetic Apron & Gloves + Chemical Respirator

Prepared by: Mike Lazar

Date: 2008

### SECTION II

#### HAZARDOUS INGREDIENTS

#### Hazardous Components (chemical & common names).

Chemical	Common	OSHA PEL	ACGIH TLV	Other Exposure Limits	CAS NO.
N-Methyl-2-Pyrrolidone			N/A (100 ppm recommended)		872-50-4
N, N-Dimethylethanolamine		5 ppm	5 ppm TLV	10 ppm PEL	108-01-0
Dipropylene Glycol Methyl Ether		100 ppm	100 ppm	N/A	34590-94-8

### SECTION III

#### PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point (°F):	212°
Melting Point (°F):	N/A
Vapor Density/ Pressure (mm Hg):	N/A
Solubility in Water:	Miscible.
Appearance and Odor:	Milky liquid.
Specific Gravity (H <sub>2</sub> O)=1):	1.02-1.04

### SECTION IV

#### FIRE & EXPLOSION DATA

Flash Point (°F):	201° F
LEL Lower/UEL Upper:	N/A
Auto Ignition Temperature:	N/A
Extinguisher Media:	Foam, carbon dioxide, water spray, dry powder Use water spray to cool containers in fire area
Special Firefighting Procedures:	Use self-contained breathing apparatus and full protective clothing.

**SECTION V**  
**PHYSICAL HAZARDS (REACTIVITY DATA)**

Stability:	Stable under normal storage and usage.
Incompatibility (Materials To Avoid):	Strong oxidizing agents like bleach and hydrogen peroxide. Prevent contact with zinc, magnesium and galvanized metals.
Hazardous Decomposition Products:	Thermal decomp. will produce carbon dioxide and may yield carbon monoxide.
Hazardous Polymerization:	Will not occur.

**SECTION VI**  
**HEALTH HAZARDS**

Signs and Symptoms of Exposure:	Excessive inhalation causes headache, dizziness, nausea and/or respiratory tract irritation. This product may be an eye irritant. Prolonged or repeated contact may cause skin irritation.
Medical conditions generally aggravated by exposure:	None known.
Carcinogens / Potential Carcinogens:	None.
National Toxicology Program:	No.
I.A.R.C. Monographs:	No.
OSHA	No.
Emergency and First Aid Procedures:	
Eye Contact:	Flush with water. Contact physician.
Skin contact:	Wash with mild soap and water.
Inhalation:	Remove to fresh air and call physician.
Ingestion:	Drink warm salt water to induce vomiting. CONTACT PHYSICIAN

**SECTION VII**  
**SPECIAL PRECAUTIONS AND SPILL / LEAK PROCEDURES**

Precautions To Be Taken In Handling And Storage:	Keep from freezing. Do not return unused portion to original container. Avoid contamination.
Other Precautions:	Face and hand protection recommended.
Steps To Be Taken In Case Material Is Released Or Spilled:	Wipe with sponge, cloth or mop.
Waste Disposal Methods: (Consult, federal, state and local regulations)	Dispose of in accordance with local, state and federal regulations.

**SECTION VIII**  
**SPECIAL PROTECTION INFORMATION / CONTROL MEASURES**

Respiratory Protection:	None if working in a ventilated area.
Ventilation:	
Local Exhaust:	
Mechanical (General):	Yes.
Other Protective Clothing/Equipment:	Eye bath and safety shower.
Work/Hygienic Practices:	This product should not be swallowed or allowed to come into contact with eyes.