

**M A T E R I A L   S A F E T Y   D A T A   S H E E T****I. IDENTIFICATION**

MANUFACTURED BY: Old Masters  
1900 Albany Place SE  
Orange City, IA 51041

REVISED: 08/06/2007  
PRINTED: 08/12/2007

**24 Hour Emergency Telephone**  
**CHEMTREC 1-800-424-9300**

General Information:  
Mon-Fri 8 AM - 5 PM  
712-737-4993

**TRADE NAME: OM Paste Wax**

**MFG. PRODUCT NUMBER: 30901**

**II. HAZARDOUS INGREDIENTS**

CAS #8052-41-3	Aliphatic Hydrocarbons	WT %: 70
ACGIH TLV: 100 ppm TWA	ACGIH STEL:	
OSHA PEL: 500 ppm TWA	OSHA CEILING:	OSHA PEAK:
VAPOR PRESSURE: 2.00 mm Hg	LEL%:	
CAS #8006-64-2	Turpentine	WT %: 10
ACGIH TLV: 100 ppm TWA	ACGIH STEL:	
OSHA PEL: 100 ppm TWA	OSHA CEILING:	OSHA PEAK:
VAPOR PRESSURE: 4mmHg@20C	LEL%: .8	

**III. PHYSICAL DATA**

BOILING RANGE: 313-338° F

EVAPORATION RATE: \* slower than ether \*

PERCENT VOLATILE BY VOLUME: 80%

WEIGHT PER GALLON: 6.4 LBS

VAPOR DENSITY: \* heavier than air \*

ACTUAL VOC (lb/gal): N/A

EPA VOC (lb/gal): N/A

EPA VOC (g/L): N/A

**IV. FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT: 39° C 102° F

LEL: Refer to Section II

FLAMMABILITY CLASSIFICATION: CLASS II

HAZARD CLASSIFICATION: \*Combustible Liquid\* CORROSIVE

EXTINGUISHING MEDIA: Water Fog, Dry Chemical, Foam, Carbon Dioxide

UNUSUAL FIRE AND EXPLOSION HAZARD: None

SPECIAL FIRE FIGHTING PROCEDURES: Use water to keep closed containers cool.

**V. HEALTH HAZARD DATA**

THRESHOLD LIMIT VALUE: See Section II.

**EFFECTS OF OVEREXPOSURE:**

ACUTE- Possible eye, skin and respiratory tract irritation.  
CHRONIC- No Data.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: \*None\*

PRIMARY ROUTE(S) OF ENTRY: Eyes, Ingestion, Skin, Inhalation

EMERGENCY AND FIRST AID PROCEDURES: Inhalation - Remove to fresh air.  
Eyes - Flush immediately with fresh water for 15 minutes.  
Call a physician.  
Skin- Wash thoroughly with soap and water

**VI. REACTIVITY DATA**

STABILITY: \*stable\* HAZARDOUS POLYMERIZATION: \*will not occur\*

INCOMPATIBILITY: Material can react violently with strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Fire, burning and welding may generate carbon monoxide.

CONDITIONS TO AVOID: None

**VII. SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: If molten, allow to solidify.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

**VIII. SPECIAL PROTECTION INFORMATION****RESPIRATORY PROTECTION:**

If air concentrations above the TLV are possible, wear a NIOSH/MSHA approved respirator.

VENTILATION: Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV and LEL of most hazardous ingredient in Section II, below acceptable limit.

PROTECTIVE GLOVES: Required for those with extreme sensitivity.

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: \*none\*

HYGIENIC PRACTICES: See Section V

### **IX. SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not store near heat, sparks, or flame.

OTHER PRECAUTIONS: \* none \*

This product contains no reportable Hazardous Air Pollutants.

---