



BENJAMIN MOORE®

STUDIO FINISHES®

ALKYD GLAZE 409

Features

- Creates an infinite variety of designs and effects on interior surfaces
- Washable finish
- Adds depth to specialty finished projects
- Can be applied over latex and oil-based coatings

Recommended For:

For producing unique effects and adding depth to all types of specialty finish projects.

For interior surfaces of wood, wallboard, cured plaster, and metal; use on new and previously painted furniture, trim, walls, and ceilings.

General Properties

A superior quality alkyd glaze formulated to produce unique effects and add depth to all types of specialty finish projects when intermixed with BENJAMIN MOORE® Color Preview® colorants, stains, or oil-based paints.

STUDIO FINISHES® Alkyd Glaze (409) is full-bodied and is easily applied over flat or satin finishes. Used alone, STUDIO FINISHES® Alkyd Glaze (409) dries to a washable, clear, low lustre finish.

Limitations:

- Do not apply when air and surface temperatures are below 50° F (10° C).

Note: All alkyd-based enamels experience a certain amount of yellowing. This effect is accelerated in dark or poorly ventilated areas. If this will produce an unwanted result, then use STUDIO FINISHES® Latex Glaze (405) for your project.

Product Information

Colors — Standard:

Clear
(Clear may be tinted with up to 4.0 fl. oz. of BENJAMIN MOORE® COLOR PREVIEW® colorants per gallon. May also be tinted or intermixed with combinations of stain or oil based paint to achieve special effects.)

— Tint Bases:

Not available

— Special Colors:

Contact your Benjamin Moore & Co. representative.

Certification

Formulated with non-photo chemically reactive solvents
Available in federally regulated areas only.

Technical Assistance

Available through your local authorized independent Benjamin Moore & Co. retailer. For the location of the retailer nearest you, call 1-800-826-2623, see www.benjaminmoore.com, or consult your local Yellow Pages.

Technical Data◇

	Clear
Vehicle Type	Alkyd
Pigment Type	None
Volume Solids	43.2%
Theoretical Coverage At Recommended Film Thickness	500 – 600 Sq. Ft.
<i>Depending on surface conditions, intermixing, and results desired.</i>	
Dry Time @ 77° F — Set To Touch (25° C) @ 50% RH	2-3 Hours 3-4 Hours 8 Hours††
	Overnight
<i>†† If a second coat is required, allow an overnight dry and lightly sand between coats.</i>	
Dries By	Evaporation, Oxidation
Viscosity	90 ± 3 KU
Flash Point	Combustible
60° Specular Gloss	Low Lustre
Surface Temperature at application	– Min. 50° F – Max. 90° F
Thin With	Do Not Thin
Clean Up Thinner	Mineral Spirits
Weight Per Gallon	9.2 lbs.
Storage Temperature	– Min. 40° F – Max. 90° F

Volatile Organic Compounds (VOC) ◇

435 Grams/Liter – 3.63 LBS/GALLON

◇ Reported values are for Clear.

Studio Finishes® Alkyd Glaze (409)

Surface Preparation

Surfaces to be finished must be clean, dry and free of wax, grease, scaling paint and mildew. Hard, glossy areas should be dulled with fine grit sandpaper to ensure proper adhesion.

New and Unpainted Plaster or Wallboard: Always prime surfaces with the appropriate BENJAMIN MOORE® FRESH START® primer.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

Tinting

STUDIO FINISHES® Alkyd Glaze (409) may be applied as received, tinted with up to 4.0 fl.oz. per gallon of BENJAMIN MOORE® COLOR PREVIEW® colorants, or intermixed with other BENJAMIN MOORE® alkyd-based products. **Water-based paint and enamels are not compatible with STUDIO FINISHES® Alkyd Glaze (409).**

Application

Immediately prior to use, stir STUDIO FINISHES® Alkyd Glaze (409). For best results, use a BENJAMIN MOORE® custom-blended china bristle brush, BENJAMIN MOORE® roller, or a similar product. This product can also be sprayed. For specialty finish applications, apply over a limited area, working in sections and stopping at natural break off points to avoid lapping.

Since the final appearance of your project will be influenced by base color and the application technique, experiment first on an isolated area or sample board to be certain the desired effect is achieved. In most faux finishing techniques the application of the glaze with a brush, roller or by spray is not the final step as these application methods do not provide the desired texture. In the final step the wet glaze is commonly re-textured with a sponge, lint free rag, plastic bag, pouncing brush or other tool to create a uniform distribution and the finished texture.

For more information on specialty finishes and techniques, visit www.benjaminmoore.com or refer to the many books and videos on the subject.

Note: All alkyd-based enamels experience a certain amount of yellowing. This effect is accelerated in dark or poorly ventilated areas. If this will produce an unwanted result, then use STUDIO FINISHES® Latex Glaze (405) for your project.

Do not apply when air and surface temperatures are below 50° F (10° C).

Thinning/Cleanup

Do not thin. Clean brushes and equipment with odorless mineral spirits.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for more information on disposal options.**

Environmental & Safety Information

Contains: Hydrotreated Naphtha
HARMFUL OR FATAL IF SWALLOWED. ASPIRATION HAZARD. CAUSES IRRITATION TO EYES, SKIN AND RESPIRATORY TRACT

Cancer Hazard: Contains Crystalline Silica which can cause cancer when in the respirable form (spray mist or sanding dust).

NOTICE: Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Keep away from heat and flame. Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves. To avoid breathing vapors or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. Aspiration Hazard. Small amounts aspirated into the respiratory system may cause mild to severe pulmonary injury. If you experience eye watering, headaches or dizziness increase fresh air or wear a properly fitted vapor/particulate NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use.

FIRST AID: If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for 15 minutes and call physician; for skin, wash with soap and water. In case of ingestion—DO NOT INDUCE VOMITING, call physician immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under “Clean Up”.

KEEP OUT OF REACH OF CHILDREN
Material Safety Data Sheets available
on request from your servicing dealer.

