



BENJAMIN MOORE®

MOORCRAFT SUPER HIDE®

LATEX EGGSHELL ENAMEL C286

Features

- Decorative and functional eggshell finish
- High hiding
- Washable
- Durable
- Easy application
- Fast dry
- Low odor
- Spatter resistant
- Soap and water cleanup
- Painted surfaces can be washed after one week

Recommended For:

For interior trim, doors, walls and ceilings; including new or previously painted wallboard, plaster, masonry and primed or previously painted wood or metal

General Properties

A quality, acrylic blended latex eggshell enamel that produces a decorative and functional finish.

Limitations:

- White and ready-made colors also suitable for limited exterior use. BENJAMIN MOORE® COLOR PREVIEW® bases are for interior use only
- Do not apply when air and surface temperatures are below 50° F (10° C)

Product Information

Colors — Standard:

White (01), Bone White (03), and White Dove (06) also available in limited areas. Linen White (70), Navajo White (73), China White (74), and Atrium White (79).

(White and off-whites may be tinted with up to 2.0 fl. oz. of BENJAMIN MOORE® COLOR PREVIEW® colorants per gallon.)

— Tint Bases:

BENJAMIN MOORE® COLOR PREVIEW® Bases 1B, 2B, 3B, & 4B.

— Special Colors:

Contact your Benjamin Moore & Co. representative.

Certification:

Master Painter Institute MPI #44

Available in all regulated areas, except South Coast

Technical Assistance

Available through your local authorized independent Benjamin Moore & Co. retailer. For the location of the retailer nearest you, call 1-800-826-2623, see www.benjaminmoore.com, or consult your local Yellow Pages.

Technical Data◇

		Pastel Base
Vehicle Type		Acrylic Blended Latex
Pigment Type		Titanium Dioxide
Volume Solids		26%
Theoretical Coverage At Recommended Film Thickness		400 – 450 Sq. Ft.
Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.		
Recommended Film Thickness	— Wet	3.8 mils
	— Dry	1.0 mils
Dry Time @ 77° F (25° C) @ 50% RH	— Set To Touch	2 Hours
	— To Recoat	4 Hours
	— To Hard Dry	24 Hours
Dries By		Evaporation., Coalescence
Viscosity		86 ± 2 KU
Flash Point		None
Gloss/Sheen		Eggshell
Surface Temperature at application	— Min.	50° F
	— Max.	90° F
Thin With		Clean Water
Clean Up Thinner		Clean Water
Weight Per Gallon		10.2 lbs.
Storage Temperature	— Min.	40° F
	— Max.	90° F

Volatile Organic Compounds (VOC) ◇

62 Grams/Liter – 0.52 LBS/GALLON

◇ Reported values are for Pastel Base. Contact Benjamin Moore & Co. for values of other bases or colors

Moorcraft Super Hide® Latex Eggshell Enamel (C286)

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming.

Difficult Substrates: Benjamin Moore & Co. offers a variety of specialty primers for use over difficult substrates such as plaster, bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your BENJAMIN MOORE® retailer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

For best hiding results, tint the primer to the approximate shade of the finish coat, especially when a significant color change is desired. **Special Note:** Certain custom colors require a Deep Color Base Primer tinted to a special prescription formula to achieve the desired color. Consult your retailer.

Previously Painted Surfaces. A primer is not required on previously painted surfaces in good condition and similar color.

Wood:

Primer: Moorcraft Super Hide® Latex Primer / Undercoater (284) or Super Spec® Alkyd Enamel Undercoater & Primer Sealer (C245).

Finish: 1 or 2 coats Moorcraft Super Hide® Latex Eggshell Enamel.

Drywall:

Primer: Moorcraft Super Hide® Latex Primer / Undercoater (284).

Finish: 1 or 2 coats Moorcraft Super Hide® Latex Eggshell Enamel.

Plaster:

Primer: Fresh Start® 100% Acrylic All-Purpose Primer (023)

Finish: 1 or 2 coats Moorcraft Super Hide® Latex Eggshell Enamel.

Masonry, New:

Rough or Pitted Masonry:

Primer: Moorcraft Super Hide® Latex Block Filler (285).

Finish: 1 or 2 coats Moorcraft Super Hide® Latex Eggshell Enamel.

Smooth Poured or Pre-cast Concrete:

Primer: Moore's® Acrylic Masonry Sealer (066) or FRESH START® All-Purpose 100% Acrylic Primer (023)

Finish: 1 or 2 coats Moorcraft Super Hide® Latex Eggshell Enamel.

Unpainted Metal (Ferrous):

Primer: IRONCLAD® Latex Low Lustre Metal & Wood Enamel (363/C363) or IRONCLAD® Alkyd Low Lustre Metal & Wood Enamel (C163)

Finish: 1 or 2 coats Moorcraft Super Hide® Latex Eggshell Enamel.

Galvanized Metal:

Primer: IRONCLAD® Latex Low Lustre Metal & Wood Enamel (363/C363)

Finish: 1 or 2 coats Moorcraft Super Hide® Latex Eggshell Enamel.

Application

Stir thoroughly before use. Apply one or two coats. For best results, use a BENJAMIN MOORE® Professional custom-blended nylon/polyester brush, BENJAMIN MOORE® Professional roller, or a similar product. This product can also be sprayed.

Spray, Airless: Fluid Pressure — 1,500 to 3,000 PSI;

Tip — .013 - .017 Orifice

Thinning/Cleanup

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents.

Clean brushes, rollers and other painting tools in warm soapy water after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust/particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air.

IN CASE OF SPILL: Absorb with inert material and dispose of as specified under **Thinning/Cleanup**

KEEP OUT OF REACH OF CHILDREN

PROTECT FROM FREEZING

Material Safety Data Sheets available on request from your servicing dealer.



Benjamin Moore & Co., 101 Paragon Drive, Montvale, NJ 07645 Tel: (201) 573-9600 Fax: (201) 573-9046 www.benjaminmoore.com M72 C286 US 12/09

BENJAMIN MOORE, COLOR PREVIEW, FRESH START, IRONCLAD, MOORE'S, MOORECRAFT SUPERCRAFT, MOORECRAFT SUPER HIDE, SUPER SPEC, and the triangle "M" symbol are registered trademarks, licensed to Benjamin Moore & Co.

© 2002, 2009 Benjamin Moore & Co.

All rights reserved