

DYNAMITE 234

- Superior wet tack and slip
- Longest open time
- Stir to desired consistency
- Ideal for pasting machines
- Strippable

Dynamite 234 Premium Grade Heavy Duty Clear Wallcovering Adhesive is recommended for hanging lightweight to heavyweight vinyl and foil wallcoverings. It is also excellent for hanging delicate and difficult wallcoverings such as silks, suedes, velours, linens, burlap, grasscloth and strings.*

*FABRICS, FOILS, STRINGS, GRASSCLOTH AND SILK – When hanging delicate wallcoverings, special care must be taken in keeping the adhesive off the face of the wallcovering as it may cause permanent discoloration. It is recommended that a sample of the selected wallcovering be tested for degree of stain resistance prior to the installation. Some wallcovering can be stained by water alone.

- Superior wet tack and slip for positioning of wallcovering
- Long open time for easier installation when booking or double cutting
- Ideal for pasting machines; stir to desired consistency
- Hangs up to 40 oz. Commercial Grade Type I, II & III

SURFACE PREPARATION Make sure wall surface is sound, clean and dry. For best results, use Dynamite All-Purpose Cleaner to prepare walls. A diluted household bleach solution also works well to clean walls. Repair or fill cracks in wall with Dynamite Non-Shrink Spackling prior to priming.

Plaster – New plaster must age at least 30 days before hanging wallcovering. Prime with Dynamite 221 or 222.

Drywall – New drywall must be wiped down with a damp cloth to remove dirt, dust, grease, wax and peeling paint. Prime with Dynamite 221 or 222.

Other Porous Surfaces – Walls must be clean, dry, smooth and structurally sound. Prime with Dynamite 221 or 222.

Glossy Surfaces – Ceramic tile, glossy paint, existing vinyl wallcoverings, Formica®, glass, plastic or baked enamel should be primed with Dynamite 221, 222 or 235.

Commercial Grade Type II & III – Prime with Dynamite 235 when hanging heavy-weight commercial grade papers.

Strippability – No primer is needed when hanging strippable, fabric-backed vinyl wallcoverings. Adhesive and primer (if used) must be completely cured prior to stripping.

DO NOT USE OVER OIL/ALKYD PAINT/PRIMER OR VARNISH UNLESS IT IS PRIMED WITH A DYNAMITE ACRYLIC PRIMER.

APPLICATION Hang wallcovering according to manufacturer's instructions. Stir to thin paste to desired consistency. **Do not dilute.** Apply evenly, making sure sufficient adhesive is on edges and corners. Apply to wallcovering with a roller, stiff brush or pasting machine. Allow proper booking time according to manufacturer's instructions. **Immediately** remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge.

COVERAGE Five gallons of adhesive will hang up to 40 single rolls. (1,400 sq. ft./5 gal.). Coverage rates can vary depending on condition of the substrate, priming and sizing, weather conditions, and method of application.

CLEAN-UP **Immediately** remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. Dry with a clean, lint-free towel to check for paste residue. Clean equipment with water.

©2009 Gardner-Gibson, Inc.
 Manufactured by: Gardner-Gibson, Inc.,
 P.O. Box 5449, Tampa, FL 33675
 www.gardner-gibson.com

See MSDS for more info

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Color	Off White
Odor	Mild
Consistency	Smooth Paste
Flash Point	Not Applicable, Water Based
Viscosity	180,000 cps
Weight per Gallon	9.7 +/- .1 lbs.
% Solids	39% +/- 1%
Recommended Storage Temperature	40 F to 100 F.
Recommended Application Range	45 F to 100 F.
Service Temperature Range	-10 F to 150 F.
Shelf Life	12 months

Approx. Shipping Weights: (Note: All approx. weights include container.)

1 gallon (3.8L)	10 lbs.
5 gallons (18.9L)	50 lbs.

PRECAUTIONS Premium Grade Heavy Duty Clear Adhesive should be stored at temperatures between 40°F and 100°F. **KEEP FROM FREEZING.** For longest life, store in controlled environment, 35°F-80°F. Do not store in direct sunlight. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. Do not reuse empty containers. Do not use in drinking water or food systems.

**CAUTION! MAY BE HARMFUL IF SWALLOWED.
 MAY CAUSE EYE, SKIN AND RESPIRATORY
 TRACT IRRITATION. KEEP OUT OF REACH OF CHILDREN.**

For emergency information call (800) 424-9300. For additional safety and hazard information, refer to the Material Safety Data Sheet for this product. Close container after each use. If sanding is done, wear a dust mask to avoid breathing of sanding dust. **FIRST AID:** Eye and skin irritant. If contact with eyes, wash with plenty of clean, room temperature water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. In case of skin contact: wash thoroughly with soap and water. If swallowed, do not induce vomiting. Call physician immediately. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

CALIF. PROP. 65 • WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC - < 1 g/L (less water & exempt)

INGREDIENTS: (>1% OF TOTAL WEIGHT): DEHYDRATED CORN SYRUP (68131-37-3), STARCH (9005-25-8), UREA (57-13-6), WATER (7732-18-5).

QUALITY PROMISE: Gardner-Gibson, Inc. promises that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, will be free of defects in material. In the unlikely event that a defect should develop, and you notify us of such a defect within 12 months of purchasing product, and provide adequate proof of purchase, we will replace the defective product at no cost to you. This promise of quality is the sole and exclusive remedy for any such defective product. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.