



1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-747-3436 Fax 712-737-3893
www.oldmastrs.com

PRODUCT INFORMATION

SANDING SEALER

PRODUCT NO.	45001, 45004, 45005, 45008
GENERIC TYPE	Alkyd Sealer/Primer
COLOR	Clear
GLOSS	Satin
SOLIDS BY WEIGHT	37 to 38%
SOLIDS BY VOLUME	27 to 28%
V.O.C.	550 grams/liter
THEORETICAL COVERAGE @ 1 MIL DFT	445 sq. ft. per gal.
COVERAGE @ RECOMMENDED DFT	300 to 450 sq. ft.
RECOMMENDED DFT PER COAT	1/2 to 1 Mil
WEIGHT PER GALLON	7.3 to 7.4 lbs./gal.
FLASH POINT	44°F Closed Cup
USE	Interior wood surfaces
VISCOSITY AT 77°F	25 to 30 sec. #2 Zahn
AVERAGE DRY TIME AT 70°F & 50% R.H.	15 minutes
RECOMMENDED THINNER	Do not thin.
APPLICATION	Pure bristle brush, foam roller or sprayer. Airless Spray: Use orifice size .009 x 20° to .011 x 20°. Conventional Spray: See Binks Spray Chart.
SURFACE PREPARATION	Must be clean, well sanded and free of dust.
CLEAN UP	Mineral Spirits

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

SANDING SEALER

DESCRIPTION: OLD MASTERS® POLY PLASTIC® SANDING SEALER, a fast-drying, modified alkyd sealer, insures an even finish and professional results on all of your interior wood projects. Using a sanding sealer eliminates the fuzz that will develop on all wood when a stain or a clear is applied. SANDING SEALER may be applied to all types of bare or stained woods, dries quickly, and sands easily to an extremely smooth finish. SANDING SEALER can be used under conventional alkyd or polyurethane clear coatings and contains no stearates.

THINNING: Do not thin. Use as packaged.

SURFACE PREPARATION: Surface must be clean, dry and free of any dirt, wax, or grease. Sand new wood to remove imperfections or saw blemishes. Remove dust particles with a tack rag. When wood is to be left natural (staining not desired), simply follow the application instructions. If staining, apply stain before using SANDING SEALER. Make sure that the stain is thoroughly dry and that there is no color pigment lying on the surface prior to application of SANDING SEALER. Restore previously finished surfaces to bare wood by removing old finishes with a paint and varnish remover or by sanding.

APPLICATION: Stir thoroughly before and occasionally during use. Apply when surface and air temperature range is between 50-90°F. Apply with pure bristle or polyester brush, or spray. Flow sealer on liberally with the grain, then level with light, even

strokes. Avoid excessive brushing. Keep area as dust free as possible until sealer is thoroughly dry. Drying time will be approximately 2-4 hours. Surface can be sanded in 3 hours depending on humidity and temperature. One coat thoroughly seals and provides uniform hold out.

After the SANDING SEALER has dried completely, smooth sealer by sanding with fine sandpaper. Be careful when sanding not to sand through the sealer film and remove the stain color. Remove any sanding dust using a tack rag, then wipe the surface with a cloth moistened with mineral spirits. Allow the surface to dry 2-4 hours, then top coat with a varnish or a polyurethane clear coating.

SPREADING RATE: Approximately 300-450 square feet per gallon depending on type and porosity of wood.

DRYING TIME: The surface will dry to touch in approximately 2-4 hours. The surface can be sanded in 3 hours depending on humidity and temperature, and may be recoated in 4 hours.

CLEAN UP: Clean up with mineral spirits, VM&P Naphtha, or paint thinner.

RECOMMENDED FINISH COAT: We recommend OLD MASTERS® solvent-based varnishes and polyurethanes. However, your projects can be top coated with most types of varnishes.

MAX. VOC: 550 grams/liter (4.6 lbs/gal)

WARNING!

FLAMMABLE LIQUID AND VAPOR.

CONTAINS PETROLEUM DISTILLATES. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks, and flame. VAPORS MAY CAUSE FLASH FIRE. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041