



1900 Albany Place SE  
P.O. Box 286  
Orange City, IA 51041

800-747-3436 Fax 712-737-3893  
www.oldmastrs.com



## PRODUCT INFORMATION

### PASTE WAX

<b>PRODUCT NO.</b>	30901
<b>GENERIC TYPE</b>	Paste Wax
<b>COLOR</b>	Crystal clear when dry
<b>GLOSS</b>	Not applicable
<b>SOLIDS BY WEIGHT</b>	20.0%
<b>SOLIDS BY VOLUME</b>	20.0%
<b>THEORETICAL COVERAGE @ 1 MIL DFT.</b>	1600 sq. ft. per gallon
<b>COVERAGE @ RECOMMENDED DFT.</b>	Not applicable
<b>RECOMMENDED DFT. PER COAT</b>	Not applicable
<b>WEIGHT PER GALLON</b>	6.4 lbs.
<b>FLASH POINT</b>	102°F. Tag Closed Cup
<b>USE</b>	Protect and enhance the beauty of wood. Use on floors, furniture, trim, etc.
<b>VISCOSITY AT 77°F</b>	Gel
<b>AVERAGE DRY TIME AT 70°F &amp; 50% R.H.</b>	15 to 30 minutes
<b>RECOMMENDED THINNER</b>	Thinning is not recommended. Use as it comes from the can.
<b>APPLICATION</b>	Use a soft, lint-free cloth or cheesecloth.
<b>SURFACE PREPARATION</b>	Be sure the surface of the finish is clean. If it appears dirty, wash it with a mild soap.
<b>CLEAN-UP</b>	Mineral spirits

**FOR THE LOVE OF WOOD®**

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



# PRODUCT INFORMATION

## **OLD MASTERS® PASTE WAX**

**DESCRIPTION:** OLD MASTERS® PASTE WAX is a special blend of waxes chosen for their excellent qualities. It contains imported carnauba wax, the hardest natural wax known to man. OLD MASTERS® PASTE WAX brings out the richness and luster in floors, furniture and woodwork. It provides outstanding durability and protection while enhancing the beauty of your wood finishes.

**RECOMMENDED USES:** Use OLD MASTERS® PASTE WAX on all fine finishes – furniture, floors, woodwork, paneling. It is recommended primarily for wood floors, but can also be used on sealed stone, vinyl, linoleum and cork floors. You can also rub the edges of your doors and drawers to keep them from sticking. Waxing the shelves in your cabinets will help prevent stains, and items won't stick during damp weather. Apply OLD MASTERS® PASTE WAX to your windowsills to protect them from rain, snow and condensation.

**CAUTIONS:** Don't use on asphalt or rubber tile floors. Solvents in this product can soften these flooring materials. Keep away from heat, sparks and open flame. Use adequate ventilation. Avoid prolonged or repeated contact with skin.

**FEATURES & BENEFITS:** OLD MASTERS® PASTE WAX aids in dusting and cleaning, and gives a fresh, clean scent to your room. It provides a protective coating that reduces friction so objects tend to slide over, rather than dig into, the finish. It helps protect your furniture and floors from scuffing and wear and keeps dust and dirt from sticking.

**DIRECTIONS FOR USE:** Apply a thin layer of wax to your wood finish using a clean, lint-free cloth or cheesecloth. Distribute the wax using circle, figure-eight or small, swirling motions, forcing the wax into the pores. Allow wax to dry 15 to 30 minutes. Test the surface with the tip of your finger before you start to buff. If it feels like a fluid, it needs to dry longer. When you rub the tip of your finger over the surface and it starts to shine, you are ready to buff. Use a power buffer or a soft, clean cotton cloth to buff. For deeper body, apply a second coat.

**FOR BEST RESULTS REMEMBER:** Thin coats dry faster and harder than thick ones. It is important that each coat be completely dry before applying the next one. If a soft layer is trapped beneath the top one, it will never harden.

## **CAUTION!**

### **COMBUSTIBLE MIXTURE**

KEEP OUT OF REACH OF CHILDREN.  
DO NOT USE NEAR OPEN FLAME.

---

### **Limited Warranty**

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

---

OLD MASTERS®  
1900 ALBANY PLACE SE  
ORANGE CITY, IA 51041