

1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-747-3436 Fax 712-737-3893
www.oldmastrs.com


PRODUCT INFORMATION

100% PURE TUNG OIL

PRODUCT NO.	90004, 90008
GENERIC TYPE	Tung Oil 100%
COLOR	Light amber
GLOSS	Not applicable
SOLIDS BY WEIGHT	99.0%
SOLIDS BY VOLUME	99.0%
V.O.C.	450 grams/liter
THEORETICAL COVERAGE @ 1 MIL DFT	1500 sq. ft. per gal.
COVERAGE @ RECOMMENDED DFT	Not applicable
RECOMMENDED DFT PER COAT	Not applicable
WEIGHT PER GALLON	7.85 lbs.
FLASH POINT	400°F Tag Closed Cup
USE	Antiques, fine furniture, bare wood
VISCOSITY AT 77°F	53 sec. #2 Zahn Cup
AVERAGE DRY TIME AT 70°F & 50% R.H.	8 to 12 hours
RECOMMENDED THINNER	Mineral Spirits
APPLICATION	Palm of hand, soft cloth, or brush
SURFACE PREPARATION	Must be clean, well sanded, and free from dust.
CLEAN UP	Mineral Spirits

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

100% PURE TUNG OIL

DESCRIPTION: For the beautiful, hand-rubbed effect achieved by master craftsmen, without the effort and time, use OLD MASTERS® 100% PURE TUNG OIL. Use on antiques, fine furniture, or bare wood—wherever a durable water and alcohol resistant oil finish is desired. Because TUNG OIL is absorbed into the wood, the finish will not crack, chip, or peel.

DIRECTIONS: Surface to be finished should be dry and dust free. Apply OLD MASTERS® 100% PURE TUNG OIL with a lint-free cloth or by bare hand. On large surfaces or in high humidity areas, thinning with mineral spirits will improve application. Up to 1 part mineral spirits to 1 part TUNG OIL may be

used; however, thinning beyond this ratio will make it non-compliant under VOC regulations. When the entire area has been coated, wipe off excess oil with a soft, lint-free cloth.

If a second coat is desired, allow the first coat to dry, then rub down with 0000 steel wool. Repeat application as above. Do not apply more coats than the wood can absorb.

For clean up, use mineral spirits or paint thinner. Promptly discard soiled rags in water-filled container to prevent spontaneous combustion.

CAUTION!

Do not take internally.

Close container after each use.

KEEP OUT OF REACH OF CHILDREN.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041