BENJAMIN MOORE®
SUPER SPEC HP®
OIL & GREASE EMULSIFIER P83

Features

- Converts oil, grease, fats, blood, or animal by-products into a soapy solution
- Residue floats up and out of surface when rinsed with water
- This conversion process reaches deep into the concrete surfaces

General Description

This cleaner is designed to convert oil, grease, fats, blood and animal by-products into a soapy solution which floats up and out of a surface during the rinsing process. It effectively removes wax off of tile or inlayed floors. Cleans tools and equipment. This emulsifying process permeates into voids, cracks, or concrete surfaces converting the oily matter into a soapy solution permitting easy removal.

Recommended For

- Concrete, wood, or metal floors
- Cleaning machinery, tanks, and equipment
- Removing oily films from cleanable, paintable surfaces

Limitations

- Keep from freezing

Product Information

Labor Saving Features

- Concentrated — must be reduced with water. See Mixing Ratio at right.
- Converts oily substances into a solution that rinses away with water.
- Conversion process cleans deep into the concrete surface permitting better coating penetration

Certification:

Formulated with non-photochemically reactive solvents.

Does not contain any ozone-depleting substances, either Class I or Class II.

Available in all regulated areas.

Technical Assistance

Available through your local authorized independent BENJAMIN MOORE® retailer. For the location of the retailer nearest you, call 1-800-826-2623, see www.benjaminmoore.com, or consult your local Yellow Pages.

Technical Data◊

Spread Rate Per Gallon of Mixed Solution		100 sq ft
Mixing Ratio (by volume)	Heavy Soil Light Soil	1 to 6 1 to 15
Reducer		Clean Water
Working Time		15 – 20 minutes
Neutralizer		Clean Water

Volatile Organic Compounds (VOC)◊
Unthinned
753 grams / Liter 6.28 LBS / Gallon

Application

To remove heavy deposits of oil, grease, blood, or fats, use a solution of 1 part Super Spec HP® P83 Oil & Grease Emulsifier mixed with 6 parts water. For light deposits of oil, grease, blood, fats, or wax, apply a solution of 1 part Super Spec HP® P83 Oil & Grease Emulsifier mixed with 15 parts water. Thoroughly scrub the surface with a stiff bristle brush until surface is clean, then rinse well with water. Repeat this process for stubborn areas or until surface is clean. Allow to dry thoroughly before coating.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Clean Up

Clean all equipment immediately after use with clean, fresh water. At the same time, flush out all fluid lines and carefully clean pressure pots. Do not allow water to remain in contact with equipment for any extended time.

Environmental, Health & Safety Information

Contains: Sodium hydroxide.

CAUSES EYE AND SKIN BURNS.

Use only with adequate ventilation. Do not breathe vapors. Ensure fresh air entry during application and drying. Avoid contact with eyes, skin and clothing. Wear chemical resistant goggles and face shield, chemical resistant gloves and protective clothing during application and cleanup. Close container after each use. Wash thoroughly after handling.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately. In case of skin contact, immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation persists. In case of ingestion, DO NOT INDUCE VOMITING, get medical attention immediately. If affected by inhalation of vapors or sanding dust, remove to fresh air.

N CASE OF SPILL — Absorb with inert material and dispose of in accordance with applicable regulations.

KEEP OUT OF REACH OF CHILDREN

Refer to Material Safety Data Sheet for additional health and safety information.

Benjamin Moore & Co., 101 Paragon Drive, Montvale, NJ 07645 Tel: (201) 573-9600 Fax: (201) 573-9046 www.benjaminmoore.com M72 P83 US 12/09

BENJAMIN MOORE, SUPER SPEC HP and the triangle "M" symbol are registered trademarks, licensed to Benjamin Moore & Co. © 2000, 2009 Benjamin Moore & Co. All rights reserved