

## HIGH HEAT ENAMELS - Spray & Brush-On including Low VOC Version

<b>DESCRIPTION</b>	Premium fast-dry formula offering superior durability and color retention for indoor and outdoor high-heat applications. For use on grills, wood burning stoves, radiators, engines and other metal items that achieve surface temperatures greater than 200°F (93 °C) and up to 1200°F (648°C).
<b>APPEARANCE</b>	Available in 5 Satin finishes: Black 7778830 spray, 7778502 Quart, 7778730 Half Pint, 233967 Gallon, 237543 Low VOC Gallon, Silver 7716830, Almond 7750830, White 7751830, and Hunter Green 7752830.
<b>FILL WEIGHT</b>	12 oz (340 g) spray. Black also available in half pint (236 ml), quart (946 ml) and gallon (3.79 l)
<b>SURFACE PREPARATION</b>	Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with commercial detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry. Scrape and wire brush rust or deteriorated coatings.
<b>APPLICATION</b>	Use in a well ventilated area. Spraying can produce a fog that will travel. Protect surrounding area, clothes and skin from overspray. Shake can vigorously for one minute after the mixing ball begins to rattle. Shake often during use. Hold can upright 12-16 inches (30-40 cm) from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface and in motion while spraying.
<b>CLEAN-UP</b>	When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other object into the stem. Throw away empty in trash pickup. Do not burn or place in home trash compactor.

### PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

	<u>SPRAY</u>	<u>BRUSH</u>
RESIN TYPE	Silicone	Modified silicone alkyd
DRY TIMES @70°F (21°C) and 50% RH		
DRY TO TOUCH	30 minutes	2 – 4 hours
HANDLE	1 – 2 hours	5 – 9 hours
RECOAT	Before 1 hour or after 48 hours	Not recommended
SHELF LIFE	5 years	5 years
<b>SAFETY</b>		
FLASH POINT	-156° F (-104° C)	80°F (26°C)
LEAD FREE		

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.