



CORONADO
P A I N T

SECTION NO. 2
ADS – 311
80 LINE
Rev. 01/11

Rust Scat®
100% Acrylic Latex High Gloss Enamel
80 Line

Type	Sheen	Theoretical Spread Rate	Recommended Application	Thinner	Clean Up
Acrylic	Gloss	350 - 450 Sq. Ft. Per Gallon*	Brush, Roller or Spray	Clean Water	Warm Soapy Water
Dry Time:		Tack Free: 30 Minutes	Recoat: 2 Hours	Full Cure: 7 – 10 Days	

PRODUCT NAME: 80 Line - Rust Scat® 100% Acrylic Latex High Gloss Enamel	Rust Scat® Gloss Acrylic Enamel is an interior-exterior finish, which is suitable for coating primed metal, wood or masonry surfaces. It is water thinned so it poses no fire hazard or objectionable odor. The acrylic resin provides excellent color and gloss retention as well as tenacious adhesion properties.	
WHERE TO USE:	Metal Wood Masonry Drywall	Interior-exterior. Rust Scat® Enamel is suitable for top-coating tanks, towers, metal buildings, signs, wood trim, furniture, walls, equipment, wherever beauty and maintenance is needed. Not recommended for unprimed wood and metal, immersion service or high corrosion areas. Not to be used as house paint on wood siding.

REGULATORY INFORMATION:	VOC/VOS STATEMENT:	OTC CATEGORY:	MPI / LEED:
	The products supported by this data sheet contain a maximum of 225 grams per liter VOC / VOS (1.88 lbs/gal.) excluding water & exempt solvents.	This product is compliant under the Ozone Transport Commission regulations as a Non-Flat High Gloss Coating.	This product is certified under MPI's #114 & #154. This product does not meet qualifications for LEED (Leadership in Energy and Environmental Design) projects.

SURFACE PREPARATION:	<p>NEW WORK: The surface to be coated must be clean and free of oil, grease, rust and other contamination that could interfere with adhesion.</p> <p>PRIMING: Ferrous Metal – Use Rust Scat® DTM Primer 180-11, 35-111, 35-147 or 35-153 Non Ferrous Metal – Use Perma Bond 100-10, 180-11 DTM Primer Galvanized – Use Perma Bond 100-10 or Grip & Seal™ 116-11, 180-11 DTM Primer Wood Interior – Use Latex Undercoat 78-11 or Alkyd Undercoat 37-11 Wood Exterior – Use Latex Primer 410-11 Drywall/Plaster – Use Latex Primer Sealer 40-11 or Grip & Seal™ 116-11 Concrete – Self Priming or Block Filler 958-11 or Masonry Sealer 48-11</p> <p>REPAINT: The surface to be painted must be clean and free of dirt, chalk, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by scrubbing with warm soapy water and thoroughly rinsed with clean water. Wax should be removed by solvent cleaning. Grease should be cleaned by using CORONADO® Sur-Prep™ I or Corotech V600-00 Oil & Grease Emulsifier. Rust must be removed by hand sanding vigorously or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer.</p>
APPLICATION:	<p>Stir Rust Scat® thoroughly with a circular, lifting motion to assure even pigment dispersion.</p> <p>Roller – Use a ¼" short nap enameling cover Brush – Use a polyester or nylon filament brush Spray – May be sprayed using conventional or airless equipment. Can be thinned with clean water, up to 15% for spraying.</p> <p>For best results use quality applicator tools. Do not sacrifice good results by using poor quality tools. Apply only when surfaces and air temperatures are between 50° F and 90°F.</p>

*NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
RESIN TYPE:	Acrylic
SOLIDS:	Weight: 48.8 ± 1.0% Volume: 36.1 ± 1.0%
WEIGHT PER GALLON:	10.3 lbs.
VISCOSITY:	92 - 97 KU (Krebs Units)
FLASH POINT:	200° F. or greater (TT-P-141, Method 4293)
SPECULAR GLOSS:	70 – 80 units @ 60 degrees
SAG RATING:	Pass 8 mils (Leneta)
REC. FILM THICKNESS:	Wet: 3.6 to 4.6 mils Dry: 1.3 to 1.7 mils
LIGHT REFLECTANCE:	95% (White or Lightest Colors)
QUALIFICATIONS:	Meets requirements for use in USDA inspected facilities Certified under MPI's #114 & #154 Meets the performance requirements of Federal Specification TT-P-1151 Certified by the CFIA (Canadian Food Inspection Agency)
CAUTIONS:	<p style="text-align: center;">WARNING!</p> <p style="text-align: center;">HARMFUL IF INHALED.</p> <p style="text-align: center;">Causes nose, throat and eye irritation. May be harmful if absorbed through skin. Harmful if swallowed.</p> <p>NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvent with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.</p> <p>Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow manufacturer's directions for respirator use. Do not get in eyes, on skin or clothing. Wash thoroughly after handling.</p> <p>First Aid: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.</p> <p>WARNING: This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.</p> <p>If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p style="text-align: center;">Obtain and read the MSDS prior to using this product. KEEP OUT OF REACH OF CHILDREN</p>