

962-SERIES GRAHAM'S EXTERIOR OIL RUSTIC STAINS

962-series Graham's Exterior Oil Rustic Stains provide rich, long-lasting color with ease of application. This product hides the wood and grain pattern, but does not obscure the texture of the wood surface. Graham's 962-series can be applied over most new or previously stained wood and hardboard surfaces. Solid colors are also for use on previously painted surfaces where a flat finish is desired. This product contains a special blend of oils and resins that impart controlled penetration and extra durability.

USES: Siding, fascia, trim and fencing. Solid Hide products are not recommended on decks, porches, steps, patios or outdoor furniture.

SURFACE PREPARATION: Surface should be clean and free of loose dirt, oil or grease. Colors as shown may vary due to smoothness, porosity or type of wood. Apply a small amount to a test area first to check color. Because the natural stains in some woods such as redwood and cedar will bleed after staining, it is recommended to use darker colors when staining these woods.

MIXING INSTRUCTIONS: Shake or mix each can thoroughly. Intermix all cans used on one job. Stir occasionally during application.

APPLICATION: Brush, roller or spray. When coating vertical or horizontal siding, apply the full length of boards to a natural break to avoid lap marks. Always work to a wet edge. Avoid applying in direct sunlight. This product may be applied at temperatures below 32.°F. However, the dry time will be slowed considerably. It may take several hours for the solvent to evaporate and several days for the coating to develop hardness.

PRODUCT SPECIFICATIONS

962-SERIES (FACTORY GROUND) RUSTIC OIL BASE EXTERIOR STAIN SOLID HIDE, WHITE & READY MIXED COLORS & BASES

<u>VEHICLE TYPE:</u>	Alkyd resin and modified linseed oil
<u>SOLVENT TYPE:</u>	Rule 66 low odor mineral spirits. VOC 350g/L max. 2.92 lbs/gal
<u>FLAMMABILITY:</u>	105°F (combustible)
<u>PIGMENT TYPES:</u>	Factory ground (fade resistant type) pigments. All pigments are free of heavy metals and toxic materials.
<u>% SOLIDS (WEIGHT):</u>	75-79
<u>% SOLIDS (VOLUME):</u>	58-62
<u>SPREAD RATE:</u>	533sq.ft/gal=3 wet mils=1.8 dry mils 400 sq.ft/gal=4 wet mils=2.4 dry mils
<u>WEIGHT PER GALLON:</u>	11.1 - 11.5 lbs.
<u>VISCOSITY:</u>	90 - 95 KU
<u>DRY TIMES:</u>	4 hours tack-free. Dry hard overnight. Will vary with temperature, humidity and porosity of surface.
<u>GLOSS:</u>	Flat

PRODUCT SPECIFICATIONS

962-50 RUSTIC OIL BASE EXTERIOR STAIN SOLID HIDE MEDIUM BASE

<u>VEHICLE TYPE:</u>	Alkyd resin and modified linseed oil
<u>SOLVENT TYPE:</u>	Rule 66 low odor mineral spirits. VOC 350g/L max. 2.92 lbs/gal
<u>FLAMMABILITY:</u>	105°F (combustible)
<u>PIGMENT TYPES:</u>	Titanium dioxide and non-hazardous silicates. All pigments are free of heavy metals and toxic materials.
<u>% SOLIDS (WEIGHT):</u>	76
<u>% SOLIDS (VOLUME):</u>	59
<u>SPREAD RATE:</u>	533sq.ft/gal=3 wet mils=1.8 dry mils 400 sq.ft/gal=4 wet mils=2.4 dry mils
<u>WEIGHT PER GALLON:</u>	11.0 lbs.
<u>VISCOSITY:</u>	90 - 95 KU
<u>DRY TIMES:</u>	6 hours tack-free. Dry hard overnight. Will vary with temperature, humidity and porosity of surface.
<u>GLOSS:</u>	Flat

PRODUCT SPECIFICATIONS

962-55 RUSTIC OIL BASE EXTERIOR STAIN
SOLID HIDE DEEP BASE

<u>VEHICLE TYPE:</u>	Alkyd resin and modified linseed oil
<u>SOLVENT TYPE:</u>	Rule 66 low odor mineral spirits. VOC 350g/L max. 2.92 lbs/gal
<u>FLAMMABILITY:</u>	105°F (combustible)
<u>PIGMENT TYPES:</u>	Titanium dioxide and non-hazardous silicates. All pigments are free of heavy metals and toxic materials.
<u>% SOLIDS (WEIGHT):</u>	73
<u>% SOLIDS (VOLUME):</u>	58
<u>SPREAD RATE:</u>	533sq.ft/gal=3 wet mils=1.8 dry mils 400 sq.ft/gal=4 wet mils=2.3 dry mils
<u>WEIGHT PER GALLON:</u>	10.1 lbs.
<u>VISCOSITY:</u>	82-85 KU
<u>DRY TIMES:</u>	6 hours tack-free. Dry hard overnight. Will vary with temperature, humidity and porosity of surface.
<u>GLOSS:</u>	Flat

PRODUCT SPECIFICATIONS

962-65 RUSTIC OIL BASE EXTERIOR STAIN SOLID HIDE ACCENT BASE

<u>VEHICLE TYPE:</u>	Alkyd resin and modified linseed oil
<u>SOLVENT TYPE:</u>	Rule 66 low odor mineral spirits. VOC 350g/L max. 2.92 lbs/gal
<u>FLAMMABILITY:</u>	105°F (combustible)
<u>PIGMENT TYPES:</u>	Titanium dioxide and non-hazardous silicates. All pigments are free of heavy metals and toxic materials.
<u>% SOLIDS (WEIGHT):</u>	72
<u>% SOLIDS (VOLUME):</u>	58
<u>SPREAD RATE:</u>	533sq.ft/gal=3 wet mils=1.8 dry mils 400 sq.ft/gal=4 wet mils=2.3 dry mils
<u>WEIGHT PER GALLON:</u>	9.6 lbs.
<u>VISCOSITY:</u>	82-85 KU
<u>DRY TIMES:</u>	6 hours tack-free. Dry hard overnight. Will vary with temperature, humidity and porosity of surface.
<u>GLOSS:</u>	Flat

PRODUCT SPECIFICATIONS

962-75 RUSTIC OIL BASE EXTERIOR STAIN SOLID HIDE NEUTRAL BASE

<u>VEHICLE TYPE:</u>	Alkyd resin and modified linseed oil
<u>SOLVENT TYPE:</u>	Rule 66 low odor mineral spirits. VOC 350g/L max. 2.92 lbs/gal
<u>FLAMMABILITY:</u>	105°F (combustible)
<u>PIGMENT TYPES:</u>	Non-hazardous silicates. All pigments are free of heavy metals and toxic materials.
<u>% SOLIDS (WEIGHT):</u>	71
<u>% SOLIDS (VOLUME):</u>	58
<u>SPREAD RATE:</u>	533sq.ft/gal=3 wet mils=1.8 dry mils 400 sq.ft/gal=4 wet mils=2.3 dry mils
<u>WEIGHT PER GALLON:</u>	9.4 lbs.
<u>VISCOSITY:</u>	82-85 KU
<u>DRY TIMES:</u>	6 hours tack-free. Dry hard overnight. Will vary with temperature, humidity and porosity of surface.
<u>GLOSS:</u>	Flat